Spec info. 12ml

Case dimension

Case weight

9.3 kg

360

Δ

Case unit

Control No.

JAN code

W330 H270 D280 mm

17000 Touch Up Paint

Touch UP

A small portion of automotive grade paint with an included brush, for repairing minor chips and scratches.

Directions:

1. Remove dust, dirt, oil, rust, etc. from the area to be treated. Finally, degrease with Silicone Off.

2. Shake well and apply promptly. If reapplication or layering is needed, first allow the previous layer to dry sufficiently.

09176 Touch Up Paint Finish Kit



This set includes a small palette, a fine-tipped brush, and a conveniently-sized portion of paint thinner. When used together, they can improve the workability and finish of touch-up paint to give a superior final appearance.

- 1. Shake paint well and put a small amount on the palette.
- 2.Use the included thinner as needed.

3.Use the fine-tipped brush to apply the paint carefully to the area to be repaired.

Directions:



07562 Wheel Touch Up Paint W62

Silver

You can easily repair minor scratches or the paint coming off with this brush type paint.

Directions

1. Remove dirt and rust from the area being applied and use Atelier 99 Silicone Off to get rid of oil.

2. Shake the bottle well and apply it quickly.

4 975759 09176 Spec info. 12ml Case dimension W 308 H 225 D 288 mm Case weight 4.6 kg

Case unit 100

Control No.

JAN code





Spec info.

08000 Body Paint - Solid

Solid



This acrylic resin gives high-gloss results just like a factory finish! It is easy to spray evenly, and features a multi-functional nozzle with 4 modes: wide, spot, horizontal, and vertical. This allows easy repair to areas of any shape and size.

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 5 minutes between each layer.

4. Leave to dry for 1 hour. Final hardening occurs by heating. Drive for 1 hour to harden through heating. Do not touch before hardening.

5. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

18000 Body Paint - Metallic, Pearl & Mica

Metallic, Pearl & Mica



This acrylic resin gives high-gloss results just like a factory finish! It is easy to spray evenly, and features a multi-functional nozzle with 4 modes: wide, spot, horizontal, and vertical. This allows easy repair to areas of any shape and size.

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 20-30 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 10 minutes between each layer.

4. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

08006 Urethane Clear



This two-component clear coat combines the excellent durability and finish of a 2K coating with the convenience of aerosol delivery. Mixing with the activator occurs inside the can, so no hassle or mess!

Directions:

1. Remove the bottom cap and press the pin downwards against a hard object such as a concrete floor. Push the pin all the way in.

- 2. Turn upside-down and leave for 5-10 minutes.
- 3. Shake well 20-30 times.

4. After spraying the colour coat, wait 2-5 minutes before applying 2K Urethane Clear. Apply over a larger area than the colour coat. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2 -3 layers to achieve an even finish. Wait 10 minutes between each layer. Note: after mixing, this paint will harden with 12 hours at 20°C. Paint cannot be used once hardened.

08002 Body Paint (Clear)

Clear



Straight acrylic resins paint gives cars a glossy shine as if they were new. It is easy to spray beautifully. Furthermore, it has a 4-way multi-function nozzle, 'wide or spot' and 'longitudinal or width ways', which allows you to repair any scratches regardless of its size.

<Clear> It gives a deep gloss and protects the metallic or pearl mica color paint.

Directions

1. Shake the can well to mix the paint.

2. 2-5 minutes after painting with Body Paint, spray it evenly on a larger area than the painted area and 15-25cm away from there, moving the can parallel to the surface.

3. Do not try to finish at once, but spray it thinly and evenly 2-3 times. Dry for 10 minutes before respraying.

* We recommend you use Body Paint (Gradator) afterward. it will prevent spray dust from occurring and produces more beautiful result.

Spec info. 300ml

Case dimension W410 H 340 D 190 mm

Case weight

17.2kg Case unit

48 Control No.

JAN code



Spec info. 320ml

Case d	limensio	on	
W 385	н 224	D 306	mr

Case weight 8.6 kg

Case unit

20

Control No.

B-44

JAN code



Spec info.
300ml
Case dimension
W408 H190 D337 mm
Case weight
10.7kg
Case unit
30
Control No.
BP-33
JAN code
4 975759 080022

Spec info.

08003 Body Paint (Primary Surfacer)

Primary Surfacer



Straight acrylic resins paint gives cars a glossy shine as if they were new. It is easy to spray beautifully. Furthermore, it has a 4-way multi-function nozzle, 'wide or spot' and 'longitudinal or width ways', which allows you to repair any scratches regardless of its size.

<Primary Surfacer> Not only does it resist rust, but it also allows the paint to adhere firmly to the top coating.

Directions

1. Remove dust, oil, wax and rust from the area being repaired in advance. We recommend you polish the desired area with a sandpaper to make it smooth in order to get more beautiful results.

Shake the can well to mix the paint every time before spraying.
 Spray it 15-25cm away from the area. Do not try to finish at once, but spray it thinly and evenly 2-3 times. Dry for 10 minutes before respraying.

4. In order to prevent the nozzle from clogging, spray it upside-down for approximately 2 seconds to let the air out after using. Afterward, wipe off the nozzle well, put the cap back on, and store.

08030 Body Paint (White Primary Surfacer)

White Primary Surfacer

Straight acrylic resins paint gives cars a glossy shine as if they were new. It is easy to spray beautifully. Furthermore, it has 4 pattern multi-function nozzle, 'wide or spot' and 'longitudinal or width ways', which allows you to repair any scratches regardless of its size.

<White Primary Surfacer> If you use this as surface preparation on white pearl color or the light color such as red or yellow, it allows you to get more beautiful result.

Directions

1. Remove dust, oil, wax and rust from the area being repaired in advance. We recommend you polish the desired area with a sandpaper to make it smooth in order to get more beautiful results.

2. Shake the can well to mix the paint every time before spraying.

Spray it 15-25cm away from the area. Do not try to finish at once, but spray it thinly and evenly 2-3 times. Dry for 10 minutes before respraying.
 In order to prevent the nozzle from clogging, spray it upside-down for approximately 2 seconds to let the air out after using. Afterward, wipe off the nozzle well, put the cap back on, and store.

08004 Body Paint (Gradator)

Gradator



Straight acrylic resins paint gives cars a glossy shine as if they were new. It is easy to spray beautifully. Furthermore, it has a 4-way multi-function nozzle, 'wide or spot' and 'longitudinal or width ways', which allows you to repair any scratches regardless of its size.

<Gradator> It obscures the boundary line between the repaired area and the original paint. It also has an effect of smoothing dust.

Directions

1. Shake the can well.

2. Within 2 minutes after painting, spray it around spray-dust evenly 15-20cm away from the desired area.

3. To prevent clogging: When finished, spray it upside-down for 2 seconds to let the air out. Afterward, wipe off the nozzle, put the cap back on and store.

08005 Body Paint (Mat Black)

Mat Black



Straight acrylic resins paint gives cars a glossy shine as if they were new. It is easy to spray beautifully. Furthermore, it has a 4-way multi-function nozzle, 'wide or spot' and 'longitudinal or width ways', which allows you to repair any scratches regardless of its size.

<Mat Black> Use this for the bumper or preventing glare on the hood.

Directions

 Shake the can well and spray it 15-20cm away from the desired area.
 To prevent clogging: When finished, spray it upside-down for 2 seconds to let the air out. Afterward, wipe off the nozzle, put the cap back on and store.

300ml
Case dimension
W408 H190 D337 mm
Case weight
10.7kg
Case unit
30
Control No.
B-34
JAN code
4 975759 080039

On a sinfa
Spec info.
300ml
Case dimension
W408 H191 D337 mm
Case weight
10.7kg
Case unit
30
Control No.
BP-31
JAN code
4 975759 080305

Spec info. 300ml

Case d	imensio	on	
W 408	н 190	D 337	mr

Case weight

	υ.	1	ĸg	
_				

Case unit

Control No

B-35

JAN code



Spec info.
300ml
Case dimension
W408 H190 D337 mm
Case weight
10.7kg
Case unit
30
Control No.
B-36
JAN code
4 975759 08005

Spec info 120ml

Case dimension

Case weight

5.2 kg

30

Case unit

Control No.

JAN code

Spec info 120ml

BP-37

W332 H157 D275 mm

08011 **Body Paint Mini - Clear**

Clear

This acrylic resin gives high-gloss results just like a factory finish! This mini can is enough to paint 2-3 layers over a 0.4-0.6 m2 area (about 4-6 sq. ft.).

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using several layers to achieve an even finish. Wait 10 minutes between each layer.

4. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

Note: We recommend use of Soft99 Body Paint Gradator to blend the resulting finish and hide any overspray.

08013 **Body Paint Mini - Primer-Surfacer**

Primer-Surfacer

This primer surfacer makes a perfect surface for preventing rust and promoting excellent adhesion of coloured paint! This mini can is enough to paint 2-3 layers over a 0.4-0.6 m2 area (about 4-6 sq. ft.).

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 10 minutes between each layer.

4. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

08014 **Body Paint Mini - White Primer-Surfacer**

White Primer-Surfacer

This primer surfacer makes a perfect surface for preventing rust and promoting excellent adhesion of paint! This white primer is perfect for white, red, or lightcoloured vehicles. This mini can is enough to paint 2-3 layers over a 0.4-0.6 m2 area (about 4-6 sq. ft.).

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 10 minutes between each layer.

4. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

08012 **Body Paint Mini - Gradator**

Gradator

The gradator is used to obscure the boundary between original and repair paint. It is also effective at blurring overspray to make it less conspicuous. This mini can is enough to gradate for a spot repair.

Directions:

1. Shake well each time before spraying. Use within 2 minutes of spraying paint. Spray from around 15-20 cm away to blur boundaries and spots of overspray

2. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

Case dime	nsior	n		
W332 H1	57 C	275	mm	
Case weigh	nt			
5.2 kg				
Case unit				
30				
Control No.				
BP-39				
JAN code				

Spec info. 120ml

Case c	limensio	on	
w 332	н 157	D 275	mm
Case v	veight		
5.2 kg			
^			

0400	-	
30		

Control No.

BP-40 JAN code



Spec info.
120ml
Case dimension
W332 H157 D275 mm
Case weight
5.2 kg
Case unit
30
Control No.
BP-38
JAN code
4 975759 080121

Spec info 420ml

Case dimension

Case weight

10.0kg

20

B-46

Case unit

Control No

JAN code

W344 H224 D276 mm

Paint Remover 08015

スプレーシンナ・

This convenient aerosol paint thinner is perfect for neatly removing paint when performing repairs.

Directions:

- 1. Mask over any areas to be protected.
- 2. Spray evenly over the paint to be removed from around 15-25 cm away.
- 3. Without allowing to dry, wipe off with a soft, clean cloth.

08075 **Under Coat**

A rust-resistant spray paint for automobile chassis and underbody, this paint creates a thick cushioning layer to prevent chips.

Directions:

- 1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.
- 2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 30-40 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 10 minutes between each laver.

4. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

08070 **Chassis Black**

A rust-resistant spray paint for automobile chassis and underbody.



Directions:

- 1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.
- 2. Shake well each time before spraying. The internal ball bearing should make a noise.
- 3. Spray from 30-40 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 10 minutes between each layer.

4. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

Spec info. 420ml

Case d	limensio	on	
W 348	н 225	d 271	mm

Case weight 9.2 ka

it

20

Control No.

B-45 JAN code



08020 **Heatproof Paint - Black**

Black



This silicone resin paint is highly heat resistant, suitable for use on high temperature parts such as the muffler or around the engine.

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 5 minutes between each layer.

4. Leave to dry for 1 hour. Final hardening occurs by heating. Drive for 1 hour to harden through heating. Do not touch before hardening.

5. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

Spec info. 300ml

Case dimension	
W408 H191 D337 mm	
Case weight	
10.7kg	
Case unit	
30	
Control No.	
BP-1	
JAN code	
4 975759 08020	

4

Spec info.
300ml
Case dimension
W410 H190 D340 mm
Case weight
10.0kg
Case unit
30
Control No.
B-30
JAN code
4 975759 080152
4 "975759"080152"

Spec info. 300ml

Heatproof Paint - Silver 08021

Silver



This silicone resin paint is highly heat resistant, suitable for use on high temperature parts such as the muffler or around the engine.

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 5 minutes between each layer.

4. Leave to dry for 1 hour. Final hardening occurs by heating. Drive for 1 hour to harden through heating. Do not touch before hardening.

5. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

08027 **Heatproof Paint - Titanium**

Titanium

This silicone resin paint is highly heat resistant, suitable for use on high temperature parts such as the muffler or around the engine.

Directions:

1. Remove dust, oil, burring, and rust from the area to be treated. Sandpaper may be used to achieve a superior finish.

2. Shake well each time before spraying. The internal ball bearing should make a noise.

3. Spray from 15-25 cm away. Do not attempt to spray all at once; spray thinly in parallel lines, using 2-3 layers to achieve an even finish. Wait 5 minutes between each laver.

4. Leave to dry for 1 hour. Final hardening occurs by heating. Drive for 1 hour to harden through heating. Do not touch before hardening.

5. To prevent clogging, discharge upside-down for 2 seconds, wipe the nozzle, replace cap, and store.

07536 Wheel Color Paint W36

Gold



this acrylic lacquer paint, you apply it directly to wheels or chrome parts. The product lineup consists of 6 colors.

Directions

Remove dust, oil, chips, and rust from the desired area. Polishing with a sandpaper in advance will help you get more beautiful result.
 Shake the can well to mix the paint, making sure the ball inside clanks.

Easy to apply yet super durable! Surface preparation is NOT necessary. With

Shake it every time before spraying.
Stand 15-25cm away from the surface and spray. Do not overspray to finish at once. Spray parallel and thinly 2-3 times for beautiful results. *Dry for 5

at once. Spray parallel and thinly 2-3 times for beautiful results. "Dry for 5 minute every time before respraying.
4. Hardens by heated after drying. Therefore, drive for more than 1 hour and heat it to make it harden after drying for more than 1 hour. Do not touch the painted area until it hardens completely.
5. In order to prevent the nozzle from clogging, spray it upside-down for about 2 seconds to let the air out after using. Afterward, wipe off the nozzle well, put the sere beautiful results.

cap back on, and store.

07537 Wheel Color Paint W37

Silver



Easy to apply yet super durable! Surface preparation is NOT necessary. With this acrylic lacquer paint, you apply it directly to wheels or chrome parts. The product lineup consists of 6 colors.

Directions

Remove dust, oil, chips, and rust from the desired area. Polishing with a sandpaper in advance will help you get more beautiful result.
 Shake the can well to mix the paint, making sure the ball inside clanks.

Shake it every time before spraying.
Stand 15-25cm away from the surface and spray. Do not overspray to finish at once. Spray parallel and thinly 2-3 times for beautiful results. *Dry for 5

minute every time before respraying. 4. Hardens by heated after drying. Therefore, drive for more than 1 hour and heat it to make it harden after drying for more than 1 hour. Do not touch the 5. In order to prevent the nozzle from clogging, spray it upside-down for about 2

seconds to let the air out after using. Afterward, wipe off the nozzle well, put the cap back on, and store.

Case dimension
W408 H191 D337 mm
Case weight
10.7kg
Case unit
30
Control No.
BP-2
JAN code
4 975759 080213



Spec info 300ml

Case d	limensio	on	
W 428	н 376	D 290	mm

Case weight

17.6kg

Case unit

48

Control No.



Spec info.
300ml
Case dimension
W428 H376 D290 mm
Case weight
17.6kg
Case unit
48
Control No.
-
JAN code

4 "975759"075370"

5

Spec info.

Wheel Color Paint W38 07538

Mat Black

Easy to apply yet super durable! Surface preparation is NOT necessary. With this acrylic lacquer paint, you apply it directly to wheels or chrome parts. The product lineup consists of 6 colors.

Directions

Remove dust, oil, chips, and rust from the desired area. Polishing with a sandpaper in advance will help you get more beautiful result.
 Shake the can well to mix the paint, making sure the ball inside clanks.

Snake the can well to mix the paint, making sure the ball inside clanks. Shake it every time before spraying.
 Stand 15-25cm away from the surface and spray. Do not overspray to finish at once. Spray parallel and thinly 2-3 times for beautiful results. *Dry for 5 minute every time before respraying.
 Hardens by heated after drying. Therefore, drive for more than 1 hour and heat it to make it harden after drying for more than 1 hour. Do not touch the painted area until it berdene completely.

painted area until it hardens completely.

5. In order to prevent the nozzle from clogging, spray it upside-down for about 2 seconds to let the air out after using. Afterward, wipe off the nozzle well, put the cap back on, and store.

07539 Wheel Color Paint W39

Black



Easy to apply yet super durable! Surface preparation is NOT necessary. With this acrylic lacquer paint, you apply it directly to wheels or chrome parts. The product lineup consists of 6 colors.

Directions

1. Remove dust, oil, chips, and rust from the desired area. Polishing with a sandpaper in advance will help you get more beautiful result.

Shake the can well to mix the paint, making sure the ball inside clanks.

Shake the can well to mix the paint, making sure the ball inside clarks. Shake it every time before spraying.
 Stand 15-25cm away from the surface and spray. Do not overspray to finish at once. Spray parallel and thinly 2-3 times for beautiful results. *Dry for 5 minute every time before respraying.
 Hardens by heated after drying. Therefore, drive for more than 1 hour and heat it to make it harden after drying for more than 1 hour. Do not touch the painted area until it barden completely.

painted area until it hardens completely. 5. In order to prevent the nozzle from clogging, spray it upside-down for about 2 seconds to let the air out after using. Afterward, wipe off the nozzle well, put the cap back on, and store.

07542 Wheel Color Paint W42

Clear



Directions

Remove dust, oil, chips, and rust from the desired area. Polishing with a sandpaper in advance will help you get more beautiful result.
 Shake the can well to mix the paint, making sure the ball inside clanks.

Shake the ball with the paint, making site the ball inside clarks.
 Shake it every time before spraying.
 Stand 15-25cm away from the surface and spray. Do not overspray to finish at once. Spray parallel and thinly 2-3 times for beautiful results. *Dry for 5

at once. Spray parallel and thinly 2-3 times for beautiful results. "Dry for 5 minute every time before respraying.
4. Hardens by heated after drying. Therefore, drive for more than 1 hour and heat it to make it harden after drying for more than 1 hour. Do not touch the painted area until it hardens completely.
5. In order to prevent the nozzle from clogging, spray it upside-down for about 2 seconds to let the air out after using. Afterward, wipe off the nozzle well, put the sere beautiful results.

cap back on, and store.

07543 Wheel Color Paint W43

Gun Metallic

Easy to apply yet super durable! Surface preparation is NOT necessary. With this acrylic lacquer paint, you apply it directly to wheels or chrome parts. The product lineup consists of 6 colors.

Directions

Remove dust, oil, chips, and rust from the desired area. Polishing with a sandpaper in advance will help you get more beautiful result.
 Shake the can well to mix the paint, making sure the ball inside clanks.

Shake it every time before spraying.
Stand 15-25cm away from the surface and spray. Do not overspray to finish at once. Spray parallel and thinly 2-3 times for beautiful results. *Dry for 5

at once. Spray parallel and thinly 2-3 times for beautiful results. Dry for 5 minute every time before respraying.
4. Hardens by heated after drying. Therefore, drive for more than 1 hour and heat it to make it harden after drying for more than 1 hour. Do not touch the painted area until it hardens completely.
5. In order to prevent the nozzle from clogging, spray it upside-down for about 2 seconds to let the air out after using. Afterward, wipe off the nozzle well, put the seconds to not even the nozzle form clogging.

cap back on, and store.

300ml
Case dimension
W428 H376 D290 mm
Case weight
17.6kg
Case unit
48
Control No.
-
JAN code
4 975759 075387

Spec info.
300ml
Case dimension
W428 H376 D290 mm
Case weight
17.6kg
Case unit
48
Control No.
-
JAN code
4 975759 075394

Spec info. 300ml

Case d	limensio	on	
w 428	н 376	D 290	mr

Case weight

17.6kg

Case unit

48 Control No.



Spec info.
300ml
Case dimension
V428 H376 D290 mm
Case weight
17.6kg
Case unit
48
Control No.
IAN code
4 975759 075431

5

(

٧ (

(

(

Spec info

09000 "Air Touch" Touch Up Paint Spray Kit



Transforming a standard brush type touch-up kit into an aerosol spray, this system makes it easy to achieve a beautiful, even finish when touching up scratches. The narrowly focussed stream allows precise treatment of scratches without unnecessary and time-consuming overspray.

Directions:

- 1. Remove dust, oil, burring, and rust from the area to be treated.
- 2. Shake the touch up paint well before removing the cap and attaching the adapter included in the Air Touch kit.
- 3. The removed brush-cap of the Touch Up paint may be inserted into the hole in this Air Touch kit package (red push-out).
- 4. Set the adapter-equipped paint tube into the top of the Air Touch system. 5. Press the top of the Air Touch to propel the paint out for treating scratches. Spray from around 6-10 cm away. Drying takes 5-10 minutes depending on ambient temperature.
- 6. The Air Touch may be cleaned by pressing the top with no paint attached.

08018 **Finish Spray For Air Touch**

Use this aerosol as the last step when repairing paint with the Soft99 Air-Touch system. It will obscure the boundary between original and repair paint, blur away overspray, and helps achieve a smooth, glossy finish.

Directions:

Spray from 15-25 cm away, over a wider area than that treated with Air-Touch.

09223 **Air-Touch Finishing Kit [Clear]**

Adding a clear coat can dramatically improve the appearance of a repair. With the included Quick Adaptor, Air Touch can be switched from colour to clear in just 3 seconds - no nozzle-washing required!

Directions:

- Directions: 1. Degrease the area to be treated with Silicone Off (sold separately). 2. Shake the paints well, and then remove the cap of both the colour and clear paints. 3. Install the Quick Adaptor to both paints. 4. After removing the original suction tube from the Air Touch head, attach the colour paint to the Air Touch using the Quick Adaptor. 5. Spray the area to be treated from around 6-10 cm away. Repeat the spraying and drying process several times to layer the paint until the original surface is no longer visible. 6. After painting the colour, remove the colour paint with its Quick Adaptor, and attach the clear coat in the same way as in Step 4. 7. After drying for 5-10 minutes (depending on temperature), test the clear for about 3 seconds against some newspaper etc. Then, spray over a slightly wider area (+5 cm in each direction) than that painted by colour. 8. Repeat the spraying and drying process several times to layer the clear until sufficient gloss appears.

of the support of the

09224 **Air-Touch Finishing Kit [Gradator]**



Finish spray for Air-Touch. Get rid of roughness around the area where sprayed Air-Touch to shade off the boundary of a surface. Attach new developed quick adaptor can replace from Touch Up Paint to

Gradator only 3 seconds. It achieves replacing without washing the nozzle.

Directions:



Quick Adopter × 2pcs (Black: for Gradator, Transparent: for Touch Up Paint)
Case dimension
W310 H215 D238 mm
Case weight
2.1 kg
Case unit
30
Control No.
B-224
JAN code
4 975759 092247

80ml
Case dimension
W 684 H 225 D 280 mm
Case weight
5.3 kg
Case unit
30
Control No.
BP-17
JAN code

4 975759 090007
Spec info.
60ml

Spec info.

Case dimension W310 H215 D238 mm

Case weight 2.1 kg Case unit 30 Control No.

Spec info.

Clear for Air-Touch: 12ml Quick Adaptor × 2 pcs



08019 Adjusting-Spray for Air Touch



Use this spray to remove paint and correct mistakes with Soft99 Air-Touch paint repair system. Spray onto a clean cloth, and wipe away the paint to be removed.

Directions:

Spec info. 80ml
Case dimension
W290 H142 D240 mm
Case weight
3.8 kg
Case unit
30
Control No.
BP-19
JAN code
4 975759 080190

09036 Spare Cap for Air Touch

A spare head for Air Touch allows the use of multiple colours of paint without the need to wash out the head.

Directions:

1. Attach to the Air Touch.

2. Spray through for 2 seconds.

3. Shake the Touch Paint well, before attaching it to the air touch and painting.





Spec info 7a

Case dimension

Case weight

W240 H210 D140 mm

08051 **Kizu Pen - White**

White



This is the ultimate quick-fix for scratches on a car body or painted plastic parts. Just draw along the scratch with the crayon type applicator to fill in and mask even deep scratches, vastly improving appearances in just a few seconds! Even though it is so simple to apply, the materials is highly durable, resisting temperatures up to 80°C and can only be removed with powerful solvents. It can also be compounded to improve the result even more!

Directions:

- 1. Remove rust, oil, burring, and water from the area to be treated.
- 2. Apply to the scratched area to fill the scratch. When layering, wait ten
- minutes between each layer.

3. Apply more than enough to fill the scratch, and then use compound later for a smooth finish. Wait at least 24 hours before using compound. Complete hardening usually takes about one week.

Kizu Pen - White Pearl 08052

White Pearl



This is the ultimate quick-fix for scratches on a car body or painted plastic parts. Just draw along the scratch with the crayon type applicator to fill in and mask even deep scratches, vastly improving appearances in just a few seconds! Even though it is so simple to apply, the materials is highly durable, resisting temperatures up to 80°C and can only be removed with powerful solvents. It can also be compounded to improve the result even more!

Directions:

- 1. Remove rust, oil, burring, and water from the area to be treated.
- 2. Apply to the scratched area to fill the scratch. When layering, wait ten minutes between each laver.

3. Apply more than enough to fill the scratch, and then use compound later for a smooth finish. Wait at least 24 hours before using compound. Complete hardening usually takes about one week.

08055 **Kizu Pen - Blue**

Blue



This is the ultimate quick-fix for scratches on a car body or painted plastic parts. Just draw along the scratch with the crayon type applicator to fill in and mask even deep scratches, vastly improving appearances in just a few seconds! Even though it is so simple to apply, the materials is highly durable, resisting temperatures up to 80°C and can only be removed with powerful solvents. It can also be compounded to improve the result even more!

Directions:

1. Remove rust, oil, burring, and water from the area to be treated. 2. Apply to the scratched area to fill the scratch. When layering, wait ten minutes between each layer.

3. Apply more than enough to fill the scratch, and then use compound later for a smooth finish. Wait at least 24 hours before using compound. Complete hardening usually takes about one week.

۱m

Spec info.

(

٧

(

(ļ



08059 **Kizu Pen - Silver**

Silver



This is the ultimate quick-fix for scratches on a car body or painted plastic parts. Just draw along the scratch with the crayon type applicator to fill in and mask even deep scratches, vastly improving appearances in just a few seconds! Even though it is so simple to apply, the materials is highly durable, resisting temperatures up to 80°C and can only be removed with powerful solvents. It can also be compounded to improve the result even more!

Directions:

1. Remove rust, oil, burring, and water from the area to be treated. 2. Apply to the scratched area to fill the scratch. When layering, wait ten minutes between each layer.

3. Apply more than enough to fill the scratch, and then use compound later for a smooth finish. Wait at least 24 hours before using compound. Complete hardening usually takes about one week.





7g		
Case dimensi	on	
v240 н210	D 140 n	r
Case weight		
1.3 kg		
Case unit		
50		
Control No.		

BP-55 JAN code

Spec info.



7g
Case dimension
W240 H210 D140 mm
Case weight
1.3 kg
Case unit
50
Control No.
BP-59
JAN code
4 975759 080596

Spec info. 7a

08060 **Kizu Pen - Gunmetal Grey**

Gunmetal Grey



This is the ultimate quick-fix for scratches on a car body or painted plastic parts. Just draw along the scratch with the crayon type applicator to fill in and mask even deep scratches, vastly improving appearances in just a few seconds! Even though it is so simple to apply, the materials is highly durable, resisting temperatures up to 80°C and can only be removed with powerful solvents. It can also be compounded to improve the result even more!

Directions:

- 1. Remove rust, oil, burring, and water from the area to be treated.
- 2. Apply to the scratched area to fill the scratch. When layering, wait ten
- minutes between each layer.

3. Apply more than enough to fill the scratch, and then use compound later for a smooth finish. Wait at least 24 hours before using compound. Complete hardening usually takes about one week.

08061 Kizu Pen - Black

Black



This is the ultimate quick-fix for scratches on a car body or painted plastic parts. Just draw along the scratch with the crayon type applicator to fill in and mask even deep scratches, vastly improving appearances in just a few seconds! Even though it is so simple to apply, the materials is highly durable, resisting temperatures up to 80°C and can only be removed with powerful solvents. It can also be compounded to improve the result even more!

Directions:

- 1. Remove rust, oil, burring, and water from the area to be treated.
- 2. Apply to the scratched area to fill the scratch. When layering, wait ten minutes between each laver.

3. Apply more than enough to fill the scratch, and then use compound later for a smooth finish. Wait at least 24 hours before using compound. Complete hardening usually takes about one week.

08062 **Kizu Pen - Matte Black**

Matte Black



This is the ultimate quick-fix for scratches on a car body or painted plastic parts. Just draw along the scratch with the crayon type applicator to fill in and mask even deep scratches, vastly improving appearances in just a few seconds! Even though it is so simple to apply, the materials is highly durable, resisting temperatures up to 80°C and can only be removed with powerful solvents. It can also be compounded to improve the result even more!

Directions:

1. Remove rust, oil, burring, and water from the area to be treated. 2. Apply to the scratched area to fill the scratch. When layering, wait ten minutes between each layer.

3. Apply more than enough to fill the scratch, and then use compound later for a smooth finish. Wait at least 24 hours before using compound. Complete hardening usually takes about one week.

50 Control No. BP-62 JAN code



02101 **Car body Repair Patch - White**

White



The perfect quick fix for a nasty scratch or chip in your paint, these ultra-thin sheets feature a flexible paint layer that combines versatility with genuine auto paint looks to massively improve appearance anywhere on the body or bumper of your vehicle. The high-powered waterproof adhesive provides excellent mechanical and weather resistance.

Directions:

1. Before applying the patch, thoroughly clean and dry the area to be treated. Be sure to remove all oils/silicone residues. We recommend Soft99 Silicone Off (sold separately) for easy degreasing. If burring, flaking or rust is present, 2. With clean hands, carefully remove the sticker from the backing sheet and

apply against the scratch. Taking care to avoid bubbles and creases, press down the sticker with a finger to adhere.

Note: Take care not to touch the adhesive surface, or allow dust or dirt to attach. Once adhered, stickers may not be reused. Stickers may be cut to shape with scissors.





Spec info. 7g

ase d	imensio	on	
240	н 210	d 140	mm

Case weight 1.3 kg

Case unit

Ca

w



Spec info. 1 sheet (80×150mm)

Case dimension

W 256 H 122 D 206 mm Case weight 1.5 kg

Case unit 50

Control No. BP-75



Spec info.

S

02102 **Car body Repair Patch - White Pearl**

White Pearl



The perfect quick fix for a nasty scratch or chip in your paint, these ultra-thin sheets feature a flexible paint layer that combines versatility with genuine auto paint looks to massively improve appearance anywhere on the body or bumper of your vehicle. The high-powered waterproof adhesive provides excellent mechanical and weather resistance.

Directions:

Before applying the patch, thoroughly clean and dry the area to be treated.
 Be sure to remove all oils/silicone residues. We recommend Soft99 Silicone Off

(sold separately) for easy degreasing. If burring, flaking or rust is present, prepare surface with sandpaper. 2. With clean hands, carefully remove the sticker from the backing sheet and apply against the scratch. Taking care to avoid bubbles and creases, press down the sticker with a finger to adhere.

Note: Take care not to touch the adhesive surface, or allow dust or dirt to attach. Once adhered, stickers may not be reused. Stickers may be cut to shape with scissors.

02103 **Car body Repair Patch - Silver Metallic**

Silver Metallic



The perfect quick fix for a nasty scratch or chip in your paint, these ultra-thin sheets feature a flexible paint layer that combines versatility with genuine auto paint looks to massively improve appearance anywhere on the body or bumper of your vehicle. The high-powered waterproof adhesive provides excellent mechanical and weather resistance.

Directions:

 Before applying the patch, thoroughly clean and dry the area to be treated. Be sure to remove all oils/silicone residues. We recommend Soft99 Silicone Off (sold separately) for easy degreasing. If burring, flaking or rust is present, 2. With clean hands, carefully remove the sticker from the backing sheet and

apply against the scratch. Taking care to avoid bubbles and creases, press down the sticker with a finger to adhere.

Note: Take care not to touch the adhesive surface, or allow dust or dirt to attach. Once adhered, stickers may not be reused. Stickers may be cut to shape with scissors.

Car body Repair Patch - Black 02104

Black



The perfect quick fix for a nasty scratch or chip in your paint, these ultra-thin sheets feature a flexible paint layer that combines versatility with genuine auto paint looks to massively improve appearance anywhere on the body or bumper of your vehicle. The high-powered waterproof adhesive provides excellent mechanical and weather resistance.

Directions:

1. Before applying the patch, thoroughly clean and dry the area to be treated. Be sure to remove all oils/silicone residues. We recommend Soft99 Silicone Off (sold separately) for easy degreasing. If burring, flaking or rust is present,

2. With clean hands, carefully remove the sticker from the backing sheet and apply against the scratch. Taking care to avoid bubbles and creases, press down the sticker with a finger to adhere.

Note: Take care not to touch the adhesive surface, or allow dust or dirt to attach. Once adhered, stickers may not be reused. Stickers may be cut to shape with scissors.

Tire Marker White 09133

White



This hard felt-tipped pen makes it easy to accurately paint tyre lettering in white.

Directions:

1. Use detergent to wash off dirt, wax, oil, and any coating before drying completely. Do not apply to hot tyres.

2. With the cap on, shake well. Remove the cap and gently press the brush onto scrap cardboard until paint comes out.

3. After testing the pen on scrap cardboard, apply to the tyre lettering. If necessary, apply another coat after drying completely.

4. If a mistake is made, do not panic. Allow to dry completely before tidying up the edges with the black pen.

1 sheet (80×150mm)	
Case dimension	
W 256 H 122 D 206 mm	
Case weight	
1.5 kg	
Case unit	
50	
Control No.	
BP-76	
JAN code	
4 975759 021025	

Spec info.
1 sheet (80×150mm)
Case dimension
W256 H122 D206 mm
Case weight
1.5 kg
Case unit
50
Control No.
BP-77
JAN code
4 975759 021032

Spec info 1 sheet (80×150mm)

Case	dimension	

W 256 H 122 D 206 mm

Case weight

1.5 kg Case unit

50

Control No.

Spec info. 8ml

BP-78 JAN code



Case dimensic	n
W 262 H 212	D 214 mm
Case weight	
2.2 kg	
Case unit	
50	
Control No.	
B-133	
JAN code	
4 97575	9 091332

Spec info.

1 sheet (80×150mm) Water proof sand paper × 1 Spatula × 1

W 545 H 214 D 240 mm

Case dimension

Case weight

2.3 kg

Case unit

02028 Alloy Wheel Repair Patch



This ultra-thin paint sheet covers up scratches easily. A flexible paint surface allows the patch to adhere firmly to any kind of curved surface. Included are sandpaper and a spatula to help you achieve a perfect fit.

Directions:

1. Scrape off any burrs from the scratching with the included sandpaper. Remove any dirt and oil from the area, and dry thoroughly. Oil may be removed with Soft99 Silicone Off.

2. With clean hands, lift the sticker from the release sheet, and attach to the patching area, taking care to avoid creases. Use the spatula to apply in awkward areas.

50 Control No. BP-21 JAN code